

SAFETY DATA SHEET

SECTION 1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier

Hydraul SH 68

1.2 Relevant identified uses of the substance or mixture and uses advised against

Hydraulic oil

1.3 Details of the supplier of the safety data sheet

Supplier	Agro Oil
	Box 30192
	104 25 Stockholm, Sweden
	Telephone +46 (0)10-556 00 00
	E-mail info@agrol.se

1.4 Emergency telephone number

Sweden

Swedish Poisons Information Centre	010-456 67 00 (Open 24/7)
Emergency	112 (Ask for the Poison Centre)

Finland

Poison Information Centre	09-471 977 (Open 24/7)
Emergency	112 (Ask for the Poison Centre)

Norway

Norwegian Poison Information Centre	22 59 13 00 (Open 24/7)
Emergency	113 (Ask for the Poison Centre)

SECTION 2. HAZARD IDENTIFICATION

2.1 Classification of the substance or mixture

The product does not meet the criteria for classification according to Regulation (EC) No 1272/2008 (CLP).

2.2 Label elements

EUH210. Safety data sheet available on request.

2.3 Other hazards

Repeated exposure may cause skin dryness.

Hydraul SH 68

SECTION 3. COMPOSITION/INFORMATION OM INGREDIENTS

3.2 Mixtures

Classification according to Regulation (EC) No 1272/2008 [CLP]

Name	EC no.	CAS no.	REACH reg no.	% (w/w)	Hazard statements
Distillates (petroleum), hydrotreated heavy paraffinic*	265-157-1	64742-54-7	01-2119484627-25	70-99	-
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based*	276-737-9	72623-86-0	01-2119474878-16	0-5	Asp. Tox. 1, H304

*Contains less than 3% DMSO extract and is therefore not classified as carcinogenic.

Other information

For a full text of hazard statements: see Section 16

SECTION 4. FIRST AID MEASURES

4.1 Description of first aid measures

After inhalation: Fresh air and rest. If difficulties in breathing get medical advice.

After eye contact: Rinse the eyes gently with water. If symptoms persist consult a doctor.

After skin contact: Take off contaminated clothing. Wash skin with soap and water

After ingestion: Rinse mouth and drink water. Do **not** induce vomiting. Contact a doctor if experiencing symptoms.

4.2 Most important symptoms and effects, both acute and delayed

Inhalation: In case of overheating, smoke and fumes appear irritating to the upper respiratory tract and lungs.

Eye: May cause mild eye irritation.

Skin: Repeated and prolonged contact may appear dehydrating on the skin and cause redness, skin cracking and eczema (dermatitis).

Ingestion: Small amounts are not expected to produce any acute or delayed symptoms. Large amounts may cause nausea and vomiting.

4.3 Indication of any immediate medical attention and special treatment needed

-

SECTION 5. FIREFIGHTING MEASURES

5.1 Extinguishing media

Suitable extinguishing media: Can be extinguished using dry powder, foam or carbon dioxide.

Unsuitable extinguishing media: Do not use direct water jet.

5.2 Special hazards arising from the substance or mixture

In case of fire, toxic and corrosive gases may develop.

Hydraul SH 68

5.3 Advice for firefighters

Precautions according to the standard procedure for chemical fires. Use water **only** to cool down containers that are exposed to fire.

SECTION 6. ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

Eliminate all sources of ignition near the spilled product. Avoid contact with eyes and skin. Ensure adequate ventilation in buildings or confined spaces.

6.2 Environmental precautions

Stop leak at the source if safe to do so. Do not allow discharge to enter sewers, watercourses or the ground. Inform the competent authorities if the product has polluted the environment (sewage, watercourses, soil or air).

6.3 Methods and material for containment and cleaning up

Contain/absorb spillages with suitable absorbent material such as sand, soil, vermiculite, diatomaceous earth or active clay. Collect in a suitable container. Disposal of waste must be in accordance with national regulations.

Spillages in water or at sea

In case of small spillages, contain product with floating barriers or other equipment. Collect spilled product by absorbing with specific floating absorbents. If possible, collect the product and contaminated material and store / dispose of in accordance with current local regulations.

6.4 Reference to other sections

See Section 8 for Exposure controls / personal protection and Section 13 for disposal considerations..

SECTION 7. HANDLING AND STORAGE

7.1 Precautions for safe handling

Avoid prolonged or repeated contact with skin.
Do not reuse soiled clothing unless laundered.
Avoid inhalation of vapours, mist or fumes.

7.2 Conditions for safe storage, including any incompatibilities

Containers must be kept tightly closed and sealed. Keep out of reach of children.

7.3 Specific end use

See Section 1.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters

Exposure limits according to National regulations

AFS 2018:1, Sweden

Substance	Cas nr	NGV ppm	NGV mg/m3	KTV ppm	KTV mg/m3	Note	Year
Oil mist, including oil fumes	-		1		3	38, 39	1990

Note:

38) When heated, some oils give rise to polycyclic aromatic hydrocarbons, which can be carcinogenic. In addition, mineral oils themselves may contain such substances.

39) For a fog of aqueous cutting fluid or the like, where substances other than oils also can be included, the value is applied as the total content of the anhydrous part. For substances with individual lower exposure limit values, they should be applied.

654/2020, Finland

Substance	Cas nr	HTP 8 hours ppm	HTP 15 minutes mg/m3	Note	Year
Oil mist	-	-	5	-	1981

Regulations concerning Action and Limit values, Norway

Name	Cas nr	ppm	mg/m3	Note	Last amended
Oil vapour	-		50		
Oil mist (mineral oil particles)	-		1		

8.2 Exposure controls

Appropriate technical measures

Ensure adequate ventilation. Methods are designed to prevent direct contact.

Personal protection

Respiratory protection: Usually not needed.

Eye/face protection: Wear eye protection (safety glasses with side shields or full face shield) when risk of splashing.

Skin protection: Wear protective gloves (nitrile or PVC) and protective clothing.

Environmental exposure control

Prevent discharges into drains.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

Physical state:	Oily liquid
Colour:	Light to brownish
Odour:	Petroleum
Melting point / freezing point:	Not available
Boiling point or initial boiling point and boiling range:	Not available

Hydraul SH 68

Flammability:

The product is not classified as flammable but can ignite and maintain a fire.

Upper / lower flammability or explosive limits:

Not available

Flash point:

195 °C

Auto-ignition temperature:

No information

Decomposition temperature:

No information

pH

No information

Kinematic viscosity:

62 mm²/s (40 °C)

Solubility:

Insoluble in water.

Partition coefficient n-octanol/water:

Not available

Vapour pressure

Not available

Density and/or relative density:

0,87 kg/l (15 °C)

Relative vapour density:

Not available

Particle characteristics:

Not applicable (liquid)

9.2 Other information

9.2.1. Information with regard to physical hazard classes

Not relevant.

9.2.2 Other safety characteristics

Not relevant.

SECTION 10. STABILITY AND REACTIVITY

10.1 Reactivity

The product is not reactive under normal conditions.

10.2 Chemical stability

The product is stable under normal conditions.

10.3 Possibility of hazardous reactions

None known.

10.4 Conditions to avoid

None specific.

10.5 Incompatible materials

The product may react with strong oxidizing agents.

10.6 Hazardous decomposition products

No hazardous decomposition products known.

SECTION 11. TOXIKOLOGICAL INFORMATION

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Not considered to be acutely toxic.

Corrosive / irritating on the skin

Repeated and prolonged contact may appear dehydrating on the skin and cause redness, skin cracking and eczema (dermatitis).

Hydraul SH 68

Serious eye damage / irritation

May cause mild eye irritation.

Respiratory / skin sensitization

Not considered to be sensitizing.

Germ cell mutagenicity

Not considered to be cause mutations in germ cells.

Carcinogenicity

Not considered to be carcinogenic.

Toxic to reproduction

Not considered to be toxic to reproduction.

Specific organ toxicity-single exposure

In case of overheating, smoke and fumes appear irritating to the upper respiratory tract and lungs.

Specific organ toxicity-repeated exposure

No information available.

Aspiration Hazard

Not considered to be an aspiration hazard.

11.2 Information on other hazards

Endocrine disrupting properties

Based on available information, this mixture contains no substance which is identified as having endocrine disrupting properties according to Regulation (EU) 2017/2100 or (EU) 2018/605 in concentrations $\geq 0.1\%$ (w/w).

SECTION 12. ECOLOGICAL INFORMATION

The product is not classified as hazardous to the environment.

12.1 Toxicity

No data available.

12.2 Persistence and degradability

Hydraul SH 68 is not rapidly biodegradable.

12.3 Bioaccumulative potential

No information available.

12.4 Mobility in soil

Product are insoluble in water and is not considered to be mobile in soil..

12.5 Results of PBT och vPvB assessment

Based on available information, this mixture contains no substance that meets the PBT or vPvB criteria according to Annex XIII to Regulation (EC) No. 1907/2006 (REACH).

12.6 Endocrine disrupting properties

Based on available information, this mixture contains no substance which is identified as having endocrine disrupting properties according to Regulation (EU) 2017/2100 or (EU) 2018/605 in concentrations $\geq 0.1\%$ (w/w).

Hydraul SH 68

12.7 Other adverse effects

None known.

SECTION 13. DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

Product

Product residues, spills etc. are classified as hazardous waste. Disposal, transportation, storage and handling of the waste must be in accordance with national regulations. Product waste must not be allowed to contaminate soil or water, or released into the environment.

Suggested waste code (EWC): Suggested waste code (EWC): 13 01 10*: Mineral-based non-chlorinated hydraulic oil.

Packaging

EWC-code: 15 01 02, Plastic packaging

EWC-code: 15 01 04, Metallic packaging

Packaging containing product residues that are not drip dry must be handled as hazardous waste and disposed of properly sealed.

EWC-code: 15 01 10*, Packaging containing residues of or contaminated by hazardous substances.

SECTION 14. TRANSPORT INFORMATION

The product is not covered by the regulations for the transport of dangerous goods.

	ADR/RID	ADN	IMDG	IATA /ICAO
14.1 UN-number or ID number	N/A	N/A	N/A	N/A
14.2 UN proper shipping name	N/A	N/A	N/A	N/A
14.3 Transport hazard class	N/A	N/A	N/A	N/A
14.4 Packing group	N/A	N/A	N/A	N/A
14.5 Environmental hazards	N/A	N/A	N/A	N/A

14.6 Special precautions for user

Not applicable

14.7 Maritime transport in bulk according to IMO instruments

Not applicable.

Hydraul SH 68

SECTION 15. REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

This safety data sheet is prepared in accordance with the EUROPEAN PARLIAMENT AND COUNCIL REGULATION (EC) No 1907/2006 of 18 December 2006 concerning the registration, evaluation, authorization and restriction of chemicals (REACH) and Commission Regulation (EU) No 2020/878 of 18 June 2020 amending the European Parliament and Council Regulation (EC) No 1907/2006 on the registration, evaluation, authorization and restriction of chemicals (REACH).

Regulations

Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substance and mixtures (CLP).

Commission Regulation (EU) No 1357/2014 of 18 December 2014 replacing Annex III to Directive 2008/98/EC of the European Parliament and of the Council on waste.

Sweden

AFS 2011:19, amended by AFS 2018:2 (Chemical risks at work)

AFS 2018:1 (Occupational exposure limits)

KIFS 2017:7 (Chemical products and Biotechnological organisms Regulation)

Finland

654/2020 (Occupational exposure limits)

715/2001 (Chemical risks at work)

Norway

Regulations concerning the design and layout of workplaces and work premises (the Workplace Regulations)

Regulations concerning action and limit values for physical and chemical agents in the working environment and classified biological agents (Regulations concerning Action and Limit values)

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

SECTION 16. OTHER INFORMATION

Please note! This safety data sheet is an English translation applicable for Sweden, Norway and Finland. A safety data sheet in local language is also available. Please refer to the Agro Oil webshop for safety data sheets in local languages. <https://webshop.agrol.se/>

Classification procedure

Test data is prioritized when classifying the product. When no test data are available the classification criteria in Regulation (EC) No 1272/2008 of the European Parliament and of the Council on classification, labelling and packaging of substances and mixtures (CLP) have been used.

Hazard statements in Section 3

H304 May be fatal if swallowed and enters airways

Abbreviations

ADN	International Carriage of Dangerous Goods by Inland Waterways
ADR	International Carriage of Dangerous Goods by Road
BCF	Bio Concentration Factor
BOD5/COD	Biological Oxygen Demand 5 days/Chemical Oxygen demand
BOD (MITI)	Biological Oxygen Demand
DNEL	Derived No Effect Level

Hydraul SH 68

EC ₅₀	Effective Concentration (concentration that gives response in 50% of test subjects)
ECHA	European Chemical Agency
EmS	Emergency Schedule Information
HTP	Exposure value, concentrations of impurities in workplace air known to be harmful.
IARC	International Agency for Research on Cancer
IATA/ICAO	IATA Dangerous goods regulation / ICAO Technical Instructions for the Safe Transport of Dangerous Goods by Air
IC ₅₀	Inhibitory Concentration (concentration that shows inhibition in 50% of the test subjects)
IMDG	International Maritime Dangerous Goods Code
KTV	Short term exposure values, normally 15 minutes
LC ₅₀	Lethal Concentration (concentration causing the death of 50% of a group of test animals)
LD ₅₀	Lethal Dose (dose causing the death of 50% of a group of test animals)
Log Pow	Partition coefficient of octanol - water
MITI	Ministry of International Trade and Industry, Japan
NGV	Long term exposure value, normally 8 hours.
NOEC	No Observed Effect Concentration
NOAEC	No Observed Adverse Effect Concentration
NOAEL	No Observed Adverse Effect Level
OECD	Organisation for Economic Co-operation and Development
PBT	Persistent Bio-accumulative and Toxic substance
PNEC	Predicted No Effect Concentration
RID	International Carriage of Dangerous Goods by Rail
STEL	Short Term Exposure Limit
SVHC	Substance of Very High Concern
TWA	Time-weighted average
vPvB	very Persistent and very Bioaccumulative

Advice on education

The user of this product should have training that is relevant to the properties of the product and relevant use.

References

Information from the supplier: Safety Data Sheet, version 23.04.2021.
Classification & Labelling Inventory Database, ECHA.
Registered substances, ECHA.

Version description

The information has been modified under the following sections in the safety data sheet: 1-16

The safety data sheet is dated 15.11.2022 and replaces the version dated 23.04.2021