RAM-233 RAM Rail Mount Adapter Kit is used with any standard 2 7/16” diameter base to convert it to rails ranging from 3/4” to 1” diameter. This kit requires drilling a 5/32” hole for heavy duty lock screw to prevent base from twisting on rail. Wrap the necessary length of rubber strip around the rail where the base will be attached. Assemble base with adapter around the rubber strip using 3-screw and nuts, drill a 5/32” hole through the adapter and rail where it won’t be visible, apply some soap to lock screw and tighten.

RMR-INS-233

RAM-233 RAM Rail Mount Adapter Kit is used with any standard 2 7/16” diameter base to convert it to rails ranging from 3/4” to 1” diameter. This kit requires drilling a 5/32” hole for heavy duty lock screw to prevent base from twisting on rail. Wrap the necessary length of rubber strip around the rail where the base will be attached. Assemble base with adapter around the rubber strip using 3-screw and nuts, drill a 5/32” hole through the adapter and rail where it won’t be visible, apply some soap to lock screw and tighten.

RMR-INS-233

RAM-233 RAM Rail Mount Adapter Kit is used with any standard 2 7/16” diameter base to convert it to rails ranging from 3/4” to 1” diameter. This kit requires drilling a 5/32” hole for heavy duty lock screw to prevent base from twisting on rail. Wrap the necessary length of rubber strip around the rail where the base will be attached. Assemble base with adapter around the rubber strip using 3-screw and nuts, drill a 5/32” hole through the adapter and rail where it won’t be visible, apply some soap to lock screw and tighten.

RMR-INS-233

RAM-233 RAM Rail Mount Adapter Kit is used with any standard 2 7/16” diameter base to convert it to rails ranging from 3/4” to 1” diameter. This kit requires drilling a 5/32” hole for heavy duty lock screw to prevent base from twisting on rail. Wrap the necessary length of rubber strip around the rail where the base will be attached. Assemble base with adapter around the rubber strip using 3-screw and nuts, drill a 5/32” hole through the adapter and rail where it won’t be visible, apply some soap to lock screw and tighten.

RMR-INS-233

RAM-233 RAM Rail Mount Adapter Kit is used with any standard 2 7/16” diameter base to convert it to rails ranging from 3/4” to 1” diameter. This kit requires drilling a 5/32” hole for heavy duty lock screw to prevent base from twisting on rail. Wrap the necessary length of rubber strip around the rail where the base will be attached. Assemble base with adapter around the rubber strip using 3-screw and nuts, drill a 5/32” hole through the adapter and rail where it won’t be visible, apply some soap to lock screw and tighten.

RMR-INS-233

RAM-233 RAM Rail Mount Adapter Kit is used with any standard 2 7/16” diameter base to convert it to rails ranging from 3/4” to 1” diameter. This kit requires drilling a 5/32” hole for heavy duty lock screw to prevent base from twisting on rail. Wrap the necessary length of rubber strip around the rail where the base will be attached. Assemble base with adapter around the rubber strip using 3-screw and nuts, drill a 5/32” hole through the adapter and rail where it won’t be visible, apply some soap to lock screw and tighten.

RMR-INS-233

RAM-233 RAM Rail Mount Adapter Kit is used with any standard 2 7/16” diameter base to convert it to rails ranging from 3/4” to 1” diameter. This kit requires drilling a 5/32” hole for heavy duty lock screw to prevent base from twisting on rail. Wrap the necessary length of rubber strip around the rail where the base will be attached. Assemble base with adapter around the rubber strip using 3-screw and nuts, drill a 5/32” hole through the adapter and rail where it won’t be visible, apply some soap to lock screw and tighten.

RMR-INS-233

RAM-233 RAM Rail Mount Adapter Kit is used with any standard 2 7/16” diameter base to convert it to rails ranging from 3/4” to 1” diameter. This kit requires drilling a 5/32” hole for heavy duty lock screw to prevent base from twisting on rail. Wrap the necessary length of rubber strip around the rail where the base will be attached. Assemble base with adapter around the rubber strip using 3-screw and nuts, drill a 5/32” hole through the adapter and rail where it won’t be visible, apply some soap to lock screw and tighten.

RMR-INS-233

RAM-233 RAM Rail Mount Adapter Kit is used with any standard 2 7/16” diameter base to convert it to rails ranging from 3/4” to 1” diameter. This kit requires drilling a 5/32” hole for heavy duty lock screw to prevent base from twisting on rail. Wrap the necessary length of rubber strip around the rail where the base will be attached. Assemble base with adapter around the rubber strip using 3-screw and nuts, drill a 5/32” hole through the adapter and rail where it won’t be visible, apply some soap to lock screw and tighten.

RMR-INS-233

RAM-233 RAM Rail Mount Adapter Kit is used with any standard 2 7/16” diameter base to convert it to rails ranging from 3/4” to 1” diameter. This kit requires drilling a 5/32” hole for heavy duty lock screw to prevent base from twisting on rail. Wrap the necessary length of rubber strip around the rail where the base will be attached. Assemble base with adapter around the rubber strip using 3-screw and nuts, drill a 5/32” hole through the adapter and rail where it won’t be visible, apply some soap to lock screw and tighten.

RMR-INS-233

RAM-233 RAM Rail Mount Adapter Kit is used with any standard 2 7/16” diameter base to convert it to rails ranging from 3/4” to 1” diameter. This kit requires drilling a 5/32” hole for heavy duty lock screw to prevent base from twisting on rail. Wrap the necessary length of rubber strip around the rail where the base will be attached. Assemble base with adapter around the rubber strip using 3-screw and nuts, drill a 5/32” hole through the adapter and rail where it won’t be visible, apply some soap to lock screw and tighten.

RMR-INS-233

RAM-233 RAM Rail Mount Adapter Kit is used with any standard 2 7/16” diameter base to convert it to rails ranging from 3/4” to 1” diameter. This kit requires drilling a 5/32” hole for heavy duty lock screw to prevent base from twisting on rail. Wrap the necessary length of rubber strip around the rail where the base will be attached. Assemble base with adapter around the rubber strip using 3-screw and nuts, drill a 5/32” hole through the adapter and rail where it won’t be visible, apply some soap to lock screw and tighten.

RMR-INS-233