






	1	2	3	4	5	6	7	8																																																									
A	<table><tr><th>Richtlänge Datum length [mm]</th><th>Längentoleranz Length tolerance [mm]</th><th>Satztoleranz Set tolerance [mm]</th></tr><tr><td>437 < Ld ≤ 500</td><td>+11/-6</td><td>2</td></tr><tr><td>500 < Ld ≤ 630</td><td>+13/-6</td><td>2</td></tr><tr><td>630 < Ld ≤ 800</td><td>+15/-7</td><td>2</td></tr><tr><td>800 < Ld ≤ 900</td><td>+17/-8</td><td>2</td></tr><tr><td>900 < Ld ≤ 1180</td><td>+19/-10</td><td>4</td></tr></table> Riemensätze müssen im Satz bestellt werden Belt sets must be ordered as a set			Richtlänge Datum length [mm]	Längentoleranz Length tolerance [mm]	Satztoleranz Set tolerance [mm]	437 < Ld ≤ 500	+11/-6	2	500 < Ld ≤ 630	+13/-6	2	630 < Ld ≤ 800	+15/-7	2	800 < Ld ≤ 900	+17/-8	2	900 < Ld ≤ 1180	+19/-10	4	Prinzip-Skizze Principle sketch 		<table><tr><th colspan="3">Profil / Section: A/13</th></tr><tr><th>b [mm]</th><th>h [mm]</th><th>α [°]</th></tr><tr><td>12,8 ± 0,8</td><td>8,0 +0,8/-0,4</td><td>39 ± 2</td></tr></table> Aufbau des Riemens: 1. Umhüllungsgewebe 2. SBR/NR Mischung 3. Polyester 4. SBR/NR Mischung V-Belt construction: 1. Standard cover fabric 2. SBR/NR compound 3. Polyester 4. SBR/NR compound			Profil / Section: A/13			b [mm]	h [mm]	α [°]	12,8 ± 0,8	8,0 +0,8/-0,4	39 ± 2	A																													
Richtlänge Datum length [mm]	Längentoleranz Length tolerance [mm]	Satztoleranz Set tolerance [mm]																																																															
437 < Ld ≤ 500	+11/-6	2																																																															
500 < Ld ≤ 630	+13/-6	2																																																															
630 < Ld ≤ 800	+15/-7	2																																																															
800 < Ld ≤ 900	+17/-8	2																																																															
900 < Ld ≤ 1180	+19/-10	4																																																															
Profil / Section: A/13																																																																	
b [mm]	h [mm]	α [°]																																																															
12,8 ± 0,8	8,0 +0,8/-0,4	39 ± 2																																																															
B									B																																																								
C	Kennzeichnungsbeispiel / Marking example: <table><tr><td>-</td><td>Made in ...</td><td>optibelt-VB A 995 L_d 13 x 965 L_i A 38</td><td>1 2</td><td>●</td></tr></table> Werkscodes / Plant code Profil und Länge / Section and Length Jahreszeichen / Year code La ≈ Li + 50 Ld ≈ Li + 30								-	Made in ...	optibelt-VB A 995 L _d 13 x 965 L _i A 38	1 2	●	C																																																			
-	Made in ...	optibelt-VB A 995 L _d 13 x 965 L _i A 38	1 2	●																																																													
D	Längen-Messbedingungen nach DIN 2215 und ISO 4183 Length measurement according to DIN 2215 and ISO 4183 <table><tr><td rowspan="10"></td><td>d_d [mm]</td><td>95,50 ± 0,05</td></tr><tr><td>U_d [mm]</td><td>300</td></tr><tr><td>d_a [mm]</td><td>102,10 ± 0,05</td></tr><tr><td>b_d [mm]</td><td>11,00</td></tr><tr><td>α [°]</td><td>34 ± 10'</td></tr><tr><td>t_{min} [mm]</td><td>12</td></tr><tr><td>Q [N]</td><td>200</td></tr><tr><td colspan="2">L_d = 2a + U_d</td></tr><tr><td colspan="2">L_a = 2a + U_a</td></tr></table> Für weitere Information siehe unsere technische Handbücher auf www.optibelt.com For further information see our technical manuals at www.optibelt.com									d _d [mm]	95,50 ± 0,05	U _d [mm]	300	d _a [mm]	102,10 ± 0,05	b _d [mm]	11,00	α [°]	34 ± 10'	t _{min} [mm]	12	Q [N]	200	L _d = 2a + U _d		L _a = 2a + U _a		<table><tr><td colspan="4"></td></tr><tr><td colspan="4">optibelt VB</td></tr><tr><td colspan="4">Profil A/13</td></tr><tr><td>4</td><td></td><td></td><td></td></tr><tr><td>3</td><td></td><td></td><td></td></tr><tr><td>2</td><td></td><td></td><td></td></tr><tr><td>1</td><td>Freigabe</td><td>08.03.2016</td><td>HGr</td></tr><tr><td>0</td><td>Erstellt</td><td>08.03.2016</td><td>MJr</td></tr><tr><td>Zust.</td><td>Änderungen</td><td>Datum</td><td>Name</td></tr></table> Dateiname: Datenblatt_optibelt VB_13.pdf					optibelt VB				Profil A/13				4				3				2				1	Freigabe	08.03.2016	HGr	0	Erstellt	08.03.2016	MJr	Zust.	Änderungen	Datum	Name	D
	d _d [mm]	95,50 ± 0,05																																																															
	U _d [mm]	300																																																															
	d _a [mm]	102,10 ± 0,05																																																															
	b _d [mm]	11,00																																																															
	α [°]	34 ± 10'																																																															
	t _{min} [mm]	12																																																															
	Q [N]	200																																																															
	L _d = 2a + U _d																																																																
	L _a = 2a + U _a																																																																
																																																																	
optibelt VB																																																																	
Profil A/13																																																																	
4																																																																	
3																																																																	
2																																																																	
1	Freigabe	08.03.2016	HGr																																																														
0	Erstellt	08.03.2016	MJr																																																														
Zust.	Änderungen	Datum	Name																																																														
	1	2	3	4	5	6	7	8																																																									

	1	2	3	4	5	6	7	8																
A	<table><tr><th>Richtlänge Datum length [mm]</th><th>Längentoleranz Length tolerance</th><th>Satztoleranz Set tolerance [mm]</th></tr><tr><td>1180 < L_d ≤ 5000</td><td>± 2 mm</td><td>± 2</td></tr></table>			Richtlänge Datum length [mm]	Längentoleranz Length tolerance	Satztoleranz Set tolerance [mm]	1180 < L _d ≤ 5000	± 2 mm	± 2	Prinzip-Skizze Principle sketch 		<table><tr><th colspan="3">Profil / Section: A/13</th></tr><tr><th>b [mm]</th><th>h [mm]</th><th>α [°]</th></tr><tr><td>12,8 ± 0,8</td><td>8,0 +0,8/-0,4</td><td>39 ± 2</td></tr></table> Aufbau des Riemens: 1. Umhüllungsgewebe 2. SBR/NR Mischung 3. Polyester 4. SBR/NR Mischung V-Belt construction: 1. Standard cover fabric 2. SBR/NR compound 3. Polyester 4. SBR/NR compound			Profil / Section: A/13			b [mm]	h [mm]	α [°]	12,8 ± 0,8	8,0 +0,8/-0,4	39 ± 2	A
Richtlänge Datum length [mm]	Längentoleranz Length tolerance	Satztoleranz Set tolerance [mm]																						
1180 < L _d ≤ 5000	± 2 mm	± 2																						
Profil / Section: A/13																								
b [mm]	h [mm]	α [°]																						
12,8 ± 0,8	8,0 +0,8/-0,4	39 ± 2																						
B									B															
C	Kennzeichnungsbeispiel / Marking example: <table><tr><td>-</td><td>Made in ...</td><td>optibelt-VB S=C plus</td><td>A 2030 L_d</td><td>13 x 2000 L_i</td><td>A 79</td><td>Antistatic ISO 1813</td><td>1 2</td><td>●</td></tr></table> Werkscod / Plant code								-	Made in ...	optibelt-VB S=C plus	A 2030 L _d	13 x 2000 L _i	A 79	Antistatic ISO 1813	1 2	●							
-	Made in ...	optibelt-VB S=C plus	A 2030 L _d	13 x 2000 L _i	A 79	Antistatic ISO 1813	1 2	●																