

IDENTIFICATION GUIDE FOR DRIVE SHAFTS



Size	Cross and bearing kit	Inboard yoke	Profile pairing	Guard tubes	Guard cones
LINE W / LINE W...E					
W 2100 W 100 E					
W 2200 W 200 E					
W 2300 W 300 E					
W 2400 W 400 E					
W 2500					
W 2600					
W 2700					
LINE W WITH WIDE ANGLE JOINT ON ONE SIDE WWE / ON TWO SIDES WWZ					
WW 2280					
WW 2380					
WW 2480					
WW 2580					
LINE P POWERDRIVE					
P 400					
P 500					
P 600					
P 700					
P 800					
LINE P WITH WIDE ANGLE JOINT ON ONE SIDE PWE / ON TWO SIDES PWZ					
PW 480					
PW 580					
PW 675					

* Profile 00a replaced by profile 00c ** Profile 00aGA replaced by profile 00cGA Profile tube: H - Hardened, V - heat-treated

IDENTIFICATION GUIDE FOR DRIVE SHAFTS



Size	Cross and bearing kit	Yoke	Replaced by size	Profile pairing	*Guard tubes	*Guard cones
IDENTIFICATION GUIDE FOR TYPES PHASED OUT (Individual components only conditional available)						
W I			W 2300			
W II			W 2400			
W 220			W 2400			
WWE/WWZ 2270			WWE/WWZ 2280			
WWE/WWZ 2370			WWE/WWZ 2380			
WWE/WWZ 220			WWE/WWZ 2480			

*SC 04/14/24/34 interchangeable with SC/SD 05/15/25/35 ** Profile 00aGA replaced by profile 00CGA

CONNECTING PROFILES

--	--	--	--	--	--

DIMENSIONS FOR GUARD TYPE

	SC SD ST		SC/SD05 D = 47	SC/SD/ST15 D = 58	SC/SD/ST25 D = 70	SC/SD35 D = 90
	PG				PG25 D = 70	
	PG		PG20 D = 85		PG30 D = 104	

FOR ALL REPAIRS
USE ONLY ORIGINAL
WALTERSCHEID SPARES.

